

WINTEX 2000

Penetrate deeper, faster.



Precision Farming Starts Here.



All soil types



Driver's seat operation



GPS enabled



Electronic depth control



Auto discard



Dual soil box

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com



Precision Farming Starts Here.

PENETRATE DEEPER. 2 LAYERS UP TO 60 CM DEEP.

Advanced programming allows you to obtain **dual-core samples** down to 60 cm with each probe cycle and **separate the soil's layers** into two soil boxes. Make a long day less tiring by controlling all functions of the **WINTX 2000** comfortably from the driver's seat.



- Homogeneous samples - a **true picture of the soil's health**
- Sample even the toughest soils, from heavily compacted soils to frozen ground.
- Adjust the depth of the probe infinitely and conveniently on a monitor, which ensures **consistent sampling depth**.
- The **WINTEX 2000** integrates with your existing GPS unit to **automatically georeference** all samples, making repeatable, year-to-year sampling seamless and simple. Use the data to create precise fertility and fertilizer prescription maps to **increase productivity in your fields**.

TECHNICAL SPECIFICATION

Depth:	0-60 cm
Layers:	1-2
Diameter probe:	26 mm with 1.5, 2.0 or 2.5 g slit
Driven by:	hydraulic hammer, hydraulic cylinder
Sampling speed:	20 sec.
Engine:	Honda GX200, 5.5 hp
Electric starter:	optional
Net weight unit:	95 kg

Volume/sample at a density 1:1:

1.5, 2.0 or 2.5 g/cm depending on the size of the probe

THE WINTEX CONTROL SYSTEM



Take control with ease - the **WINTEX control system** lets you adjust settings, enter presets, and manage every function effortlessly from one intuitive interface.

MOUNTING OPTIONS

UTV: side or back

ATV: back - depending on the load capacity

Pickup

Tractor, three-point hitch

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com

