WINTEX 3000

Triple split-core probe



Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted +45 97990800, contact@wintexagro.com wintexagro.com



Precision Farming Starts Here.

PENETRATE DEEPER. 3 LAYERS UP TO 90 CM DEEP.

Advanced programming allows you to obtain **triple-core samples** down to 90 cm with each probe cycle and **separate the soil's layers** into three boxes. Make a long day less tiring by controlling all functions of the **WINTX 3000** comfortably from the driver's seat.



- Homogeneous samples a true picture of the soil's health
- Sample even the toughtest soils, from heavily compated soils to frozen ground.
- Adjust the depth of the probe infinetly and conveniently on a monitor, which ensures consistent sampling depth.
- The **WINTEX 3000** integrates with your existing GPS unit to **automatically georefernce** all samples, making repeatable, year-to-year sampling seamless and simple. Use the data to create precise fertility and fertilizer prescription maps to **increase productivity in your fields**.

TECHNICAL SPECIFICATION

Depth: 0-90 cm **Layers**: 1-3

Diameter probe: 26 mm with 1.5, 2.0 or 2.5 g slit **Driven by:** hydraulic hammer, hydraulic cylinder

Sampling speed: 30 sec.

Engine: Honda GX200, 5.5 hp

Electric starter: optional Net weight unit: 112 kg

Volume/sample at a density 1:1:

1.5, 2.0 or 2.5 g/cm depending on the size of the probe

THE WINTEX CONTROL SYSTEM



Take control with ease - the **WINTEX control system** lets you adjust settings, enter presets, and manage every function effortlessly form one intuitive interface.

MOUNTING OPTIONS

UTV: side or back

ATV: back - depending on the load capacity

Pickup

Tractor, three-point hitch

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted +45 97990800, contact@wintexagro.com wintexagro.com

