

WINTEX 2500

Penetrate deeper, faster.

WintexAgro

Precision Farming starts here.



All soil types



Driver's seat operation



GPS enabled



Electronic depth control



Auto discard



Triple soil box

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com



Precision Farming Starts Here.

PENETRATE DEEPER. 3 LAYERS UP TO 60 CM DEEP.

Advanced programming allows you to obtain **triple-core samples** down to 60 cm with each probe cycle and **separate the soil's layers** into three boxes. Make a long day less tiring by controlling all functions of the **WINTX 2500** comfortably from the driver's seat.



- Homogeneous samples - a **true picture of the soil's health**
- Sample even the toughest soils, from heavily compacted soils to frozen ground.
- Adjust the depth of the probe infinitely and conveniently on a monitor, which ensures **consistent sampling depth**.
- The **WINTX 2500** integrates with your existing GPS unit to **automatically georeference** all samples, making repeatable, year-to-year sampling seamless and simple. Use the data to create precise fertility and fertilizer prescription maps to **increase productivity in your fields**.

TECHNICAL SPECIFICATION

Depth:	0-60 cm
Layers:	1-3
Diameter probe:	26 mm with 1.5, 2.0 or 2.5 g slit
Driven by:	hydraulic hammer, hydraulic cylinder
Sampling speed:	20 sec.
Engine:	Honda GX200, 5.5 hp
Electric starter:	optional
Net weight unit:	110 kg

Volume/sample at a density 1:1:

1.5, 2.0 or 2.5 g/cm depending on the size of the probe

THE WINTEX CONTROL SYSTEM



Take control with ease - the **WINTEX control system** lets you adjust settings, enter presets, and manage every function effortlessly from one intuitive interface.

MOUNTING OPTIONS

UTV: side or back

ATV: back - depending on the load capacity

Pickup

Tractor, three-point hitch

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com

